

TYRES

Product group	Tyres
Item number	10000687
Valid tyre size	600 / 70 R 30
LI / SI / PR	155 A8 / 152 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Factor



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Agrimax Factor is a new type of 70 series radial tyre for tillage tractors.
- Its tractor pattern with extended lugs provides good ride comfort.
- The reduced lug angle allows for reduced rolling resistance.
- The large contact area ensures smooth running.
- The strong polyester carcass provides excellent lateral stability and steering response even at higher speeds.

Technical Informations

Item number	10000687
EAN	8903094070152
Valid tyre size	600 / 70 R 30
LI / SI / PR	155 A8 / 152 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Factor
Carcass properties	E-Ready
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	174,11
Recommended rim size	DW20B
Permitted rim size	DW18L, W18L
Maximum air pressure [bar].	1,60
Section width (mm)	611
Tread width (mm)	570
Outer diameter of tyre [mm].	1602
Stat. radius (SLR) [mm]	722
Speed Radius Index (SRI)	750
Rolling circumference [mm].	4765
Tread depth (mm)	57,0
Number of lugs	19x2
E-Ready	Yes

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A8	3875	40		1,60	
152 D	3550	65		1,60	