

## TYRES

Product group	Tyres
Item number	10000688
Valid tyre size	710 / 70 R 42
LI / SI / PR	176 A8 / 173 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Factor



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- The BKT Agrimax Factor is a new type of 70 series radial tyre for tillage tractors.
- Its tractor pattern with extended lugs provides good ride comfort.
- The reduced lug angle allows for reduced rolling resistance.
- The large contact area ensures smooth running.
- The strong polyester carcass provides excellent lateral stability and steering response even at higher speeds.

**Technical Informations**

<b>Item number</b>	10000688
<b>EAN</b>	8903094070169
<b>Valid tyre size</b>	710 / 70 R 42
<b>LI / SI / PR</b>	176 A8 / 173 D
<b>TL/TT</b>	TL
<b>Brand</b>	BKT
<b>Tread pattern</b>	Agrimax Factor
<b>Carcass properties</b>	E-Ready
<b>Antistatic</b>	No
<b>Tyre colour</b>	Black
<b>ECE regulation number</b>	ECE 106
<b>Nettogewicht [kg] (gültig)</b>	321,85
<b>Recommended rim size</b>	DW23B
<b>Permitted rim size</b>	DW25B
<b>Maximum air pressure [bar].</b>	2,40
<b>Section width (mm)</b>	716
<b>Tread width (mm)</b>	675
<b>Outer diameter of tyre [mm].</b>	2061
<b>Stat. radius (SLR) [mm]</b>	935
<b>Speed Radius Index (SRI)</b>	975
<b>Rolling circumference [mm].</b>	6198
<b>Tread depth (mm)</b>	58,0
<b>Number of lugs</b>	21x2
<b>E-Ready</b>	Yes

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 A8	7100	40		2,40	
173 D	6500	65		2,40	