

TYRES

Product group	Tyres
Item number	10001538
Valid tyre size	24 R 21
LI / SI / PR	176 G, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 331



Notes and features

- The BKT Earthmax SR 331 is an MPT radial tyre for multi-purpose and emergency vehicles.
- Its unique block tread maximises the ground contact area to provide very good handling and ride comfort in all conditions.
- The non-directional tread offers very good flotation, traction and self-cleaning properties.
- The tyre is well suited for all surfaces, including soft, sandy or muddy ground.
- The all-steel carcass and steel belt design guarantee a long service life and very good protection against cracks or punctures.

Technical Informations

Item number	10001538
EAN	8903094067671
Valid tyre size	24 R 21
LI / SI / PR	176 G, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 331
M+S	M+S
Carcass properties	POR
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	198,03
Recommended rim size	18.0
Maximum air pressure [bar].	5,90
Section width (mm)	606
Outer diameter of tyre [mm].	1382
Stat. radius (SLR) [mm]	628
Rolling circumference [mm].	4194
Tread depth (mm)	24,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 G	7100	90		5,90	