

## **TYRES**

| Product group   | Tyres          |
|-----------------|----------------|
| Item number     | 10001555       |
| Valid tyre size | 710 / 70 R 38  |
| LI / SI / PR    | 169 A8 / 166 D |
| TL/TT           | TL             |
| Brand           | BKT            |
| Tread pattern   | Agrimax Factor |





## Notes and features

- The BKT Agrimax Factor is a new type of 70 series radial tyre for tillage tractors.
- Its tractor pattern with extended lugs provides good ride comfort.
- The reduced lug angle allows for reduced rolling resistance.
- The large contact area ensures smooth running.
- The strong polyester carcass provides excellent lateral stability and steering response even at higher speeds.



## **Technical Informations**

| Item number                  | 10001555       |
|------------------------------|----------------|
| EAN                          | 8903094071142  |
| Valid tyre size              | 710 / 70 R 38  |
| LI / SI / PR                 | 169 A8 / 166 D |
| TL/TT                        | TL             |
| Brand                        | BKT            |
| Tread pattern                | Agrimax Factor |
| TRA Code                     | R1-W           |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | ECE 106        |
| Nettogewicht [kg] (gültig)   | 285,18         |
| Recommended rim size         | DW23B          |
| Maximum air pressure [bar].  | 1,60           |
| Section width (mm)           | 716            |
| Outer diameter of tyre [mm]. | 1959           |
| Stat. radius (SLR) [mm]      | 866            |
| Speed Radius Index (SRI)     | 925            |
| Rolling circumference [mm].  | 5800           |
| E-Ready                      | Yes            |

## **Load capacity**

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 169 A8 | 5800               | 40           |               | 1,60                        |              |
| 166 D  | 5300               | 65           |               | 1,60                        |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.