

TYRES

Product group	Tyres
Item number	10001583
Valid tyre size	9.00 R 20
LI / SI / PR	160 A5
TL/TT	TL
Brand	BKT
Tread pattern	Liftmax LM 81



Bohnenkamp
■ ■ ● Moving Professionals

BKT
GROWING TOGETHER

Notes and features

- The BKT Liftmax LM 81 is a newly-developed industrial radial tyre produced according to the latest technology for heavy forklifts and terminal tractors.
- The strong all-steel casing and reinforced sidewall provide excellent stability and handling in lift mode.
- Its aggressive and robust tread pattern and rubber compound provide excellent traction and a long service life.
- The radial casing absorbs ground unevenness and thus increases high ride comfort and the operator's safety and prevents fatigue.
- All Liftmax LM 81 are designed to dissipate static charge from the vehicle.

Technical Informations

Item number	10001583
EAN	8903094073177
Valid tyre size	9.00 R 20
LI / SI / PR	160 A5
TL/TT	TL
Brand	BKT
Tread pattern	Liftmax LM 81
Antistatic	Yes
Tyre colour	Black
Nettogewicht [kg] (gültig)	86,87
Recommended rim size	7.0
Permitted rim size	7.5
Maximum air pressure [bar].	10,00
Section width (mm)	255
Outer diameter of tyre [mm].	1028
Tread depth (mm)	33,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 A5	4500	25	Steering wheel	10,00	
	5850	25	Load wheel	10,00	