

TYRES

Product group	Tyres
Item number	10001610
Valid tyre size	405 / 70 R 20
LI / SI / PR	168 A2 / 152 J
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 525



Notes and features

- The BKT Multimax MP 525 is an MPT radial tyre for telehandlers, skid steer loaders and graders in agro-industrial use.
- Its all-steel carcass allows high load capacities and higher speeds on and off the road.
- The non-directional tread provides outstanding traction and self-cleaning properties.
- The strong side wall provides exceptional stability when lifting.
- The cut- and puncture-resistant rubber compound protects against damage to ensure a long service life.

Technical Informations

Item number	10001610
EAN	8903094072873
Valid tyre size	405 / 70 R 20
Alternative size 1	16.0/70R20
LI / SI / PR	168 A2 / 152 J
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 525
M+S	M+S
Carcass properties	POR,All-Steel
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	75,75
Recommended rim size	13
Permitted rim size	11, 12, 13SDC
Maximum air pressure [bar].	6,00
Section width (mm)	405
Outer diameter of tyre [mm].	1076
Stat. radius (SLR) [mm]	482
Rolling circumference [mm].	3260
Tread depth (mm)	23,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 A2	5600	10		6,00	
152 J	3550	100		6,00	