

TYRES

Product group	Tyres
Item number	10001619
Valid tyre size	500 / 50 R 17
LI / SI / PR	147 D
TL/TT	TL
Brand	BKT
Tread pattern	Trac Super



Notes and features

- Radial traction tyre specifically designed for operations on grassland, as well as for mixed on-road and off-road use.
- Aggressive, offset traction tread pattern offers reliable traction in all conditions, especially on slopes.
- Large contact area provides additional stability in use.
- Steel-belt reinforced casing makes the tyre even more stable and protects against punctures.

Technical Informations

Item number	10001619
EAN	8903094073337
Valid tyre size	500 / 50 R 17
LI / SI / PR	147 D
TL/TT	TL
Brand	BKT
Tread pattern	Trac Super
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	64,12
Recommended rim size	16.00
Maximum air pressure [bar].	4,50
Section width (mm)	490
Outer diameter of tyre [mm].	940
Stat. radius (SLR) [mm]	425
Speed Radius Index (SRI)	450
Rolling circumference [mm].	2850
Tread depth (mm)	22,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 D	3075	65		4,50	