

TYRES

Product group	Tyres
Item number	19211273
Valid tyre size	20 x 8.00 - 10
LI / SI / PR	74 A6 / 85 A6, 6 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K513



Notes and features

- The Kenda K513 is a tyre for the professional maintenance of lawns.
- Its tread blocks have sipes to provide good traction and consequently optimum soil protection.
- The tyre can be used on slopes and provide good grip in dry as well as wet weather conditions.
- Due to the large contact area and the durable rubber compound, the tyre is particularly low-wear and durable.

Technical Informations

Item number	19211273
EAN	5707562470344
Valid tyre size	20 x 8.00 - 10
LI / SI / PR	74 A6 / 85 A6, 6 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K513
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	6,58
Recommended rim size	6.00I
Maximum air pressure [bar].	3,00
Section width (mm)	218
Outer diameter of tyre [mm].	518
Rolling circumference [mm].	1546
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
74 A6	375	30	Drive Wheel	3,00	
85 A6	515	30	Free Rolling	3,00	